



# APLIC'ENDUIT : FIXATION PAR NOYAGE DANS UN MUR ENDUIT

## GAMME DE RACCORDEMENTS

À GLISSEMENT

À SERTIR

À VISER

À SOUDER

MULTICOUCHE  
U - H - TH

COLORIS :

LAITON

NICKEL

MANGANÈSE

ANTHRACITE

SABLE

NOIR



| RACCORDEMENT              | Ø     | 1660 | 1680 | 1690 | 1700 | 1710 | 1720 |
|---------------------------|-------|------|------|------|------|------|------|
| À GLISSEMENT              | 12    | 1660 | 1680 | 1690 | 1700 | 1710 | 1720 |
|                           | 16    | 1661 | 1681 | 1691 | 1701 | 1711 | 1721 |
| À SERTIR                  | 12    | 1662 | 1682 | 1692 | 1702 | 1712 | 1722 |
|                           | 16    | 1663 | 1683 | 1693 | 1703 | 1713 | 1723 |
| À VISER                   | F1/2" | 1664 | 1684 | 1694 | 1704 | 1714 | 1724 |
| À SOUDER                  | 14&16 | 1665 | 1685 | 1695 | 1705 | 1715 | 1725 |
| MULTICOUCHE<br>U - H - TH | 16x2  | 1666 | 1686 | 1696 | 1706 | 1716 | 1726 |

INSTALLATION



Après pose et dans le cadre de la norme d'isolation RT 2012, il peut être utile d'obturer les passages d'air par l'injection de mousse expansive à l'arrière du montage.